


# Essential Sliding Door (80mm, 140mm)

## Installation Details

BRICK VENEER CONSTRUCTION - HEAD & JAMB DETAIL



NOTE:  
FOR SITE CLASSIFICATIONS OF UP TO AND INCLUDING 'N6' OR SIMILAR, FIXINGS ARE TO BE AT 450mm CENTRE MAXIMUM, FOR SITUATIONS IN EXCESS OF THIS THE FIXINGS ARE TO BE AT 300mm CENTRES MAXIMUM. FIXING SIZE TO BE EQUIVALENT TO A  $\phi$  2.2mm STEEL NAIL MINIMUM.

PRODUCT NO: ESS 80 & 140 SD

DATE: 02/04/15

DRAWING NO: ESS-SD-02-01


ISSUE: A

DRAWN: DJH

SCALE: 1 : 3



BRICK VENEER CONSTRUCTION - SILL & JAMB DETAIL AT FLOOR LEVEL



NOTE:  
FOR SITE CLASSIFICATIONS OF UP TO AND INCLUDING 'N6' OR SIMILAR, FIXINGS ARE TO BE AT 450mm CENTRE MAXIMUM, FOR SITUATIONS IN EXCESS OF THIS THE FIXINGS ARE TO BE AT 300mm CENTRES MAXIMUM. FIXING SIZE TO BE EQUIVALENT TO A  $\phi$  2.2mm STEEL NAIL MINIMUM.

PRODUCT NO: ESS 80 & 140 SD

DATE: 02/04/15


DRAWING NO: ESS-SD-02-02

ISSUE: A

DRAWN: DJH

SCALE: 1 : 3

CLADDING CONSTRUCTION - HEAD & JAMB DETAIL



NOTE:  
FOR SITE CLASSIFICATIONS OF UP TO AND INCLUDING 'N6' OR SIMILAR, FIXINGS ARE TO BE AT 450mm CENTRE MAXIMUM, FOR SITUATIONS IN EXCESS OF THIS THE FIXINGS ARE TO BE AT 300mm CENTRES MAXIMUM. FIXING SIZE TO BE EQUIVALENT TO A  $\phi$  2.2mm STEEL NAIL MINIMUM.

PRODUCT NO: ESS 80 & 140 SD

DATE: 02/04/15

DRAWING NO: ESS-SD-02-03


ISSUE: A

DRAWN: DJH

SCALE: 1 : 3



CLADDING CONSTRUCTION - SILL & JAMB DETAIL AT FLOOR LEVEL



NOTE:  
FOR SITE CLASSIFICATIONS OF UP TO AND INCLUDING 'N6' OR SIMILAR, FIXINGS ARE TO BE AT 450mm CENTRE MAXIMUM, FOR SITUATIONS IN EXCESS OF THIS THE FIXINGS ARE TO BE AT 300mm CENTRES MAXIMUM. FIXING SIZE TO BE EQUIVALENT TO A  $\varnothing$  2.2mm STEEL NAIL MINIMUM.

PRODUCT NO: ESS 80 & 140 SD

DATE: 02/04/15

DRAWING NO: ESS-SD-02-04


ISSUE: A

DRAWN: DJH

SCALE: 1 : 3



CAVITY BRICK CONSTRUCTION - HEAD & JAMB DETAIL



NOTE:  
FOR SITE CLASSIFICATIONS OF UP TO AND INCLUDING 'N6' OR SIMILAR, FIXINGS ARE TO BE AT 450mm CENTRE MAXIMUM, FOR SITUATIONS IN EXCESS OF THIS THE FIXINGS ARE TO BE AT 300mm CENTRES MAXIMUM. FIXING SIZE TO BE EQUIVALENT TO A  $\phi$ 2.2mm STEEL NAIL MINIMUM.

PRODUCT NO: ESS 80 & 140 SD

DATE: 02/04/15

DRAWING NO: ESS-SD-02-05


ISSUE: A

DRAWN: DJH

SCALE: 1 : 3



CAVITY BRICK CONSTRUCTION - SILL & JAMB DETAIL AT FLOOR LEVEL



NOTE:  
FOR SITE CLASSIFICATIONS OF UP TO AND INCLUDING 'N6' OR SIMILAR, FIXINGS ARE TO BE AT 450mm CENTRE MAXIMUM, FOR SITUATIONS IN EXCESS OF THIS THE FIXINGS ARE TO BE AT 300mm CENTRES MAXIMUM. FIXING SIZE TO BE EQUIVALENT TO A  $\phi$  2.2mm STEEL NAIL MINIMUM.

PRODUCT NO: ESS 80 & 140 SD

DATE: 02/04/15


DRAWING NO: ESS-SD-02-06

ISSUE: A

DRAWN: DJH

SCALE: 1 : 3

BLOCKWORK CONSTRUCTION - HEAD & JAMB DETAIL



NOTE:  
SURFACE OF BLOCKS TO WINDOW OPENING MUST BE TANKED WITH A SUITABLE SEALER TO PREVENT INGRESS OF MOISTURE. ENSURE SURFACES TO BE SEALED ARE SOUND, CLEAN, DRY AND FREE FROM ANY CONTAMINANTS BEFORE SEALING.

FOR SITE CLASSIFICATIONS OF UP TO AND INCLUDING 'N6' OR SIMILAR, FIXINGS ARE TO BE AT 450mm CENTRE MAXIMUM, FOR SITUATIONS IN EXCESS OF THIS THE FIXINGS ARE TO BE AT 300mm CENTRES MAXIMUM. FIXING SIZE TO BE EQUIVALENT TO A  $\varnothing 2.2$ mm STEEL NAIL MINIMUM.

PRODUCT NO: ESS 80 & 140 SD

DATE: 02/04/15

DRAWING NO: ESS-SD-02-07


ISSUE: A

DRAWN: DJH

SCALE: 1 : 3



BLOCKWORK CONSTRUCTION - SILL & JAMB DETAIL AT FLOOR LEVEL



NOTE:  
SURFACE OF BLOCKS TO WINDOW OPENING MUST BE TANKED WITH A SUITABLE SEALER TO PREVENT INGRESS OF MOISTURE. ENSURE SURFACES TO BE SEALED ARE SOUND, CLEAN, DRY AND FREE FROM ANY CONTAMINANTS BEFORE SEALING.

FOR SITE CLASSIFICATIONS OF UP TO AND INCLUDING 'N6' OR SIMILAR, FIXINGS ARE TO BE AT 450mm CENTRE MAXIMUM, FOR SITUATIONS IN EXCESS OF THIS THE FIXINGS ARE TO BE AT 300mm CENTRES MAXIMUM. FIXING SIZE TO BE EQUIVALENT TO A  $\varnothing 2.2$ mm STEEL NAIL MINIMUM.

PRODUCT NO: ESS 80 & 140 SD

DATE: 02/04/15


DRAWING NO: ESS-SD-02-08

ISSUE: A

DRAWN: DJH

SCALE: 1 : 3

CONCRETE CONSTRUCTION - HEAD & JAMB DETAIL



NOTE:  
SURFACE OF CONCRETE TO WINDOW OPENING MUST BE TANKED WITH A SUITABLE SEALER TO PREVENT INGRESS OF MOISTURE. ENSURE SURFACES TO BE SEALED ARE SOUND, CLEAN, DRY AND FREE FROM ANY CONTAMINANTS BEFORE SEALING.

FIXING TYPES & CENTRES TO BE PROJECT SPECIFIC, REFER TO SPECIFICATION AND/OR ENGINEER.

PRODUCT NO: ESS 80 & 140 SD

DATE: 02/04/15

DRAWING NO: ESS-SD-02-09


ISSUE: A

DRAWN: DJH

SCALE: 1 : 3



CONCRETE CONSTRUCTION - SILL & JAMB DETAIL AT FLOOR LEVEL



NOTE:  
SURFACE OF CONCRETE TO WINDOW OPENING MUST BE TANKED WITH A SUITABLE SEALER TO PREVENT INGRESS OF MOISTURE. ENSURE SURFACES TO BE SEALED ARE SOUND, CLEAN, DRY AND FREE FROM ANY CONTAMINANTS BEFORE SEALING.

FIXING TYPES & CENTRES TO BE PROJECT SPECIFIC, REFER TO SPECIFICATION AND/OR ENGINEER.

PRODUCT NO: ESS 80 & 140 SD

DATE: 02/04/15

DRAWING NO: ESS-SD-02-10


ISSUE: A

DRAWN: DJH


SCALE: 1 : 3



### TYPICAL SUBSILL DAM ANGLE INSTALLATION



1. INSTALL SUBSILL INTO OPENING WITH DAM ANGLE FITTED. PACK SUBSILL LEVEL THEN FIX TO STRUCTURE. SEAL SUBSILL ENDS TO STRUCTURE.



2. APPLY SEALANT TO VERTICAL FACE OF DAM ANGLE AND ALSO TO THE FLOOR OF THE SUBSILL. POSITION DAM ANGLE AGAINST STRUCTURE. SEAL ALL JOINTS BETWEEN ANGLE AND SUBSILL. SEAL ALL JOINTS BETWEEN ANGLE AND SUBSILL. SEAL OVER FIXINGS AND UNDER SUB SILL TO STRUCTURE.

PRODUCT NO: ESS 80 & 140 SD

DATE: 02/04/15


DRAWING NO: ESS-SD-02-11

ISSUE: A

DRAWN: DJH

SCALE: 1 : 4

TYPICAL SUBSILL DAM ANGLE INSTALLATION WITH THE FIXING & TRIM ANGLES



PRODUCT NO: ESS 80 & 140 SD

DRAWING NO: ESS-SD-02-12

DRAWN: DJH

DATE: 02/04/15

ISSUE: A

SCALE: 1 : 1.5



**Bradnam's**  
windows & doors